

SPECIFICATION FOR DRIZIT® SKIRTED OIL ONLY BOOMS



	0112/3/S
Size	15cm dia x 3m, 20cm skirt
Colour	Grey
Pack Quantity	2
Pack Wt (gross)	14.8 kg
Pack Size	70 x 55 x 40 cm
Sorbency (pack)	70 - 92 litres

Sorbency: Lower figure test method to BS 7959-1:2004 using SAE10W40 motor oil.

Higher figure based on high viscosity liquid with no drain

- Outer Casing:** Nonwoven based on thermally bonded continuous bi-component filaments, PET core and PA-6 skin, 10 dtex per filament. Tensile strength: 280N (5mm strip/EN ISO 10319).
High UV resistance.
- Skirt:** Black PE tube (250 microns), with chain for ballast, eyelet to locate joining ropes, and solid mass adhesive strip for joining
- Filler:** Polypropylene or other fibres.
- Fitted with:** 6mm UV stabilized polypropylene rope along length, with 100cm tails for fixing, and 0.5m tails for joining.
- Pack Type:** Bag
- Compatibility:** Water-repellency exceeds requirements of BS 7959-2:2000.
May be safely used with all liquids immiscible with water, such as hydrocarbons, solvents, mineral oils etc.
Before any use in a spill situation a proper risk assessment should be carried out and all hazardous properties of the liquid or dangerous reactions taken into account.
- Fire Resistance:** Good. (Physically flame-retardant)
Incinerable to low ash.
- Disposal:** Used sorbents may be disposed of by landfill or incineration, in accordance with local and national regulations, taking into account the classification of the liquid absorbed.
- Safety Data:** Refer to our Material Safety Data Sheet.
This product is non-toxic to users and to aquatic life.
Further technical advice is available if required.
- Note:** All weights, dimensions, and other figures quoted are approximate.

Revision Date: 01-07-2016

Spillcare Manufacture

Environmental Services

Liquid Monitoring & Control


Industrial Marine



LEADING PROVIDER OF PRACTICAL POLLUTION
CONTROL PRODUCTS AND SERVICES

VAT No. 203 3006 36 Registered in England No. 472058

SPECIFICATION FOR DRIZIT® EXTREME OIL ONLY NETTED BOOMS



	0112/NET/1.5	0105/NET/3	0112/NET/3	0112/NET/6
Size	20cm dia x 1.5m	12.5cm dia x 3m	20cm dia x 3m	20cm dia x 6m
Colour	White	White	White	White
Pack Quantity	4	4	4	2
Pack Wt (gross)	10.0 kg	9.2 kg	17.4 kg	17.4 kg
Pack Size	40 dia x 70 cm	70 dia x 60 cm	75 dia x 45 cm	75 dia x 45 cm
Sorbency (pack)	157 - 172 litres	120 - 130 litres	314 - 344 litres	314 - 344 litres

Sorbency: Lower figure test method to BS 7959-1:2004 using SAE10W40 motor oil. Higher figure based on high viscosity liquid with no drain

- Outer Casing:** Nylon netting.
- Inner Casing:** Non-woven white polypropylene material.
- Filler:** Polypropylene or other fibres.
- Fitted with:** 6mm UV stabilized polypropylene rope along length.
Steel clip and ring for joining
- Pack Type:** Bag
- Compatibility:** Water-repellency exceeds requirements of BS 7959-2:2000.
May be safely used with all liquids immiscible with water, such as hydrocarbons, solvents, mineral oils etc.
Before any use in a spill situation a proper risk assessment should be carried out and all hazardous properties of the liquid or dangerous reactions taken into account.
- Disposal:** Used sorbents may be disposed of by landfill or incineration, in accordance with local and national regulations, taking into account the classification of the liquid absorbed.
- Safety Data:** Refer to our Material Safety Data Sheet.
This product is non-toxic to users and to aquatic life.
Further technical advice is available if required.
- Note:** All weights, dimensions, and other figures quoted are approximate.


Revision Date: 04-07-2016

Spillcare Manufacture

Environmental Services

Liquid Monitoring & Control

Industrial Marine

 LEADING PROVIDER OF PRACTICAL POLLUTION
CONTROL PRODUCTS AND SERVICES

VAT No. 203 3006 36 Registered in England No. 472058

SPECIFICATION FOR DRIZIT® 350GSM OIL ONLY ROLLS (WHITE)



	LRW35MB001BG
Size	100cm x 42m
Perforations	n/a
Colour	White
Pack Quantity	1
Pack Wt (gross)	14.7 kg
Pack Size	100 x 40 x 40 cm
Sorbency (pack)	300 - 400 litres

Sorbency: Lower figure test method to BS 7959-1:2004 using SAE10W40 motor oil. Higher figure based on high viscosity liquid with no drain

Composition: 100% Polypropylene
Meltblown

Basis Wt: 350gsm

Pack Type: Bag

Compatibility: Water-repellency exceeds requirements of BS 7959-2:2000.
May be safely used with all liquids immiscible with water, such as hydrocarbons, solvents, mineral oils etc.
Before any use in a spill situation a proper risk assessment should be carried out and all hazardous properties of the liquid or dangerous reactions taken into account.

Fire Resistance: Good. (Physically flame-retardant)
Incinerable to zero ash.

Disposal: Used sorbents may be disposed of by landfill or incineration, in accordance with local and national regulations, taking into account the classification of the liquid absorbed.

Safety Data: Refer to our Material Safety Data Sheet.
This product is non-toxic to users and to aquatic life.
Further technical advice is available if required.

Note: All weights, dimensions, and other figures quoted are approximate.

Revision Date: 01-07-2016

Spillcare Manufacture

Environmental Services

Liquid Monitoring & Control


Industrial Marine



LEADING PROVIDER OF PRACTICAL POLLUTION
CONTROL PRODUCTS AND SERVICES

VAT No. 203 3006 36 Registered in England No. 472058

SPECIFICATION FOR DRIZIT® EXTREME 240GSM OIL ONLY PADS (WHITE)



	PDW24SL100BG
Size	40cm x 50cm
Perforations	Along at 25cm
Colour	White
Pack Quantity	100
Pack Wt (gross)	4.8 kg
Pack Size	50 x 40 x 27 cm
Sorbency (pack)	88 - 117 litres

Sorbency: Lower figure test method to BS 7959-1:2004 using SAE10W40 motor oil. Higher figure based on high viscosity liquid with no drain

- Composition:** 100% Polypropylene
Meltblown, ultrasonically bonded, spunbond laminated on one side
- Basis Wt:** 17gsm spunbond 223gsm meltblown
- Pack Type:** Bag
- Compatibility:** Water-repellency exceeds requirements of BS 7959-2:2000.
May be safely used with all liquids immiscible with water, such as hydrocarbons, solvents, mineral oils etc.
Before any use in a spill situation a proper risk assessment should be carried out and all hazardous properties of the liquid or dangerous reactions taken into account.
- Fire Resistance:** Good. (Physically flame-retardant)
Incinerable to zero ash.
- Disposal:** Used sorbents may be disposed of by landfill or incineration, in accordance with local and national regulations, taking into account the classification of the liquid absorbed.
- Safety Data:** Refer to our Material Safety Data Sheet.
This product is non-toxic to users and to aquatic life.
Further technical advice is available if required.
- Note:** All weights, dimensions, and other figures quoted are approximate.

Revision Date: 01-07-2016

Spillcare Manufacture

Environmental Services

Liquid Monitoring & Control


Industrial Marine



LEADING PROVIDER OF PRACTICAL POLLUTION
CONTROL PRODUCTS AND SERVICES

VAT No. 203 3006 36 Registered in England No. 472058

SPECIFICATION FOR DRIZIT® 350GSM OIL ONLY PADS (WHITE)



PDW35MB100BG	
Size	40cm x 52cm
Perforations	n/a
Colour	White
Pack Quantity	100
Pack Wt (gross)	7.3 kg
Pack Size	40 x 52 x 40 cm
Sorbency (pack)	150 - 200 litres

Sorbency: Lower figure test method to BS 7959-1:2004 using SAE10W40 motor oil. Higher figure based on high viscosity liquid with no drain

Composition: 100% Polypropylene
Meltblown

Basis Wt: 350gsm

Pack Type: Bag

Compatibility: Water-repellency exceeds requirements of BS 7959-2:2000.
May be safely used with all liquids immiscible with water, such as hydrocarbons, solvents, mineral oils etc.
Before any use in a spill situation a proper risk assessment should be carried out and all hazardous properties of the liquid or dangerous reactions taken into account.

Fire Resistance: Good. (Physically flame-retardant)
Incinerable to zero ash.

Disposal: Used sorbents may be disposed of by landfill or incineration, in accordance with local and national regulations, taking into account the classification of the liquid absorbed.

Safety Data: Refer to our Material Safety Data Sheet.
This product is non-toxic to users and to aquatic life.
Further technical advice is available if required.

Note: All weights, dimensions, and other figures quoted are approximate.

Revision Date: 01-07-2016

Spillcare Manufacture

Environmental Services

Liquid Monitoring & Control

Industrial Marine



LEADING PROVIDER OF PRACTICAL POLLUTION
CONTROL PRODUCTS AND SERVICES

VAT No. 203 3006 36 Registered in England No. 472058

SPECIFICATION FOR DRIZIT® OIL ONLY CUSHIONS (WHITE)



	0111/20/W	0110/W
Size	33 x 21 x 6 cm	55 x 35 x 10 cm
Colour	White	White
Pack Quantity	20	10
Pack Wt (gross)	5.3 kg	7.5 kg
Pack Size	60 x 50 x 30 cm	50 x 45 x 40 cm
Sorbency (pack)	85 - 84 litres	135 - 150 litres

Sorbency: Lower figure test method to BS 7959-1:2004 using SAE10W40 motor oil. Higher figure based on high viscosity liquid with no drain

- Outer Casing:** 100% polypropylene spun-bonded
Tensile strength (mean): 400N (200mm strip/EN ISO 10319)
UV resistant
- Filler:** Polypropylene and other fibres
- Pack Type:** Bag
- Compatibility:** Water-repellency exceeds requirements of BS 7959-2:2000.
May be safely used with all liquids immiscible with water, such as hydrocarbons, solvents, mineral oils etc.
Before any use in a spill situation a proper risk assessment should be carried out and all hazardous properties of the liquid or dangerous reactions taken into account.
- Fire Resistance:** Good. (Physically flame-retardant)
Incinerable to zero ash.
- Disposal:** Used sorbents may be disposed of by landfill or incineration, in accordance with local and national regulations, taking into account the classification of the liquid absorbed.
- Safety Data:** Refer to our Material Safety Data Sheet.
This product is non-toxic to users and to aquatic life.
Further technical advice is available if required.
- Note:** All weights, dimensions, and other figures quoted are approximate.

Revision Date: 01-07-2016

Spillcare Manufacture

Environmental Services

Liquid Monitoring & Control

Industrial Marine



LEADING PROVIDER OF PRACTICAL POLLUTION
CONTROL PRODUCTS AND SERVICES

VAT No. 203 3006 36 Registered in England No. 472058

SPECIFICATION FOR DRIZIT® CLAY GRANULES



	0399	0399/16
Colour	Grey	Grey
Pack Wt (gross)	13 kg	16 kg
Pack Volume	15 litres	20 litres
Pack Size	50 x 35 x 10 cm	45 x 60.5 x 10.5 cm
Qty per pallet	91	70
Sorbency (pack)	8 - 13 litres	10 - 17 litres

Sorbency: Lower figure test method to BS 7959-1:2004 using SAE10W40 motor oil. Higher figure based on high viscosity liquid with no drain.

Composition: Calcium Sulphate (gypsum) >90%

Particle Size: 1 – 5mm (typical)

Pack Type: Bag

Compatibility: May be safely used with non-aggressive aqueous solutions and liquids immiscible with water, such as hydrocarbons, solvents, mineral oils.

Before any use in a spill situation a proper risk assessment should be carried out and all hazardous properties of the liquid or dangerous reactions taken into account.

Fire Resistance: Non-combustible.

Disposal: Used sorbents may be disposed of by landfill or incineration, in accordance with local and national regulations, taking into account the classification of the liquid absorbed.

Safety Data: Refer to our Material Safety Data Sheet.

This product is non-toxic to users and to aquatic life.

Further technical advice is available if required.

Note: All weights, dimensions, and other figures quoted are approximate.

Revision Date: 05-07-2016

Spillcare Manufacture

Environmental Services

Liquid Monitoring & Control

Industrial Marine



LEADING PROVIDER OF PRACTICAL POLLUTION
CONTROL PRODUCTS AND SERVICES

VAT No. 203 3006 36 Registered in England No. 472058